



Stilo

TECHNICAL SPECIFICATION

STILO

Cover	resistant to weather conditions; anodized aluminium
Ingress protection	IP54
Impact protection	IK10
Residual current protection*	RCD B / Enelion RCM B + RCD A
Charging connector	AC Type 2; cable range 5m; EN 62196-1
Energy meter	built-in
MID Energy meter*	installed in a dedicated intermediate box
Main switch*	installed in a dedicated intermediate box
Communication module Bridge OCPP 1.6*	offline / Wi-Fi, Ethernet / LTE (GSM)
Minimal signal quality requirements	WiFi: -60 dBm / GSM: -85 dBm
User authorization*	RFID + 2 cards (MIFARE / ISO14443) / FreeCharge
User interface	LED Light bar
Charging points parameters	3-phase electric power
Line-to-line voltage	400V
The frequency of the charging point	50 Hz
Charging current/power	3 x 32A / 22kW
Charging voltage	3 x 230V AC
Branding: laser engraved pattern*	according to the customer's needs
Operating temperature	-25°C / + 55°C
Storage temperature	-40°C / + 80°C
Max. above sea level	2 000m
Height (mm)	430
Width (mm)	185
Depth (mm)	56
Weight	5,5 kg

*Optional equipment

REV 03-2024